

Baltic ForBio, WP 2, GA 2.4

Information about thinning demonstration area where biofuel and roundwood is produced (601-186-12)

Information about stand

Basic information

State	Latvia
Region	Kurzeme
Stand ID	601-186-12
Area (ha)	3.4
Thinning year / season	2016/spring
Торіс	Thinning with Vimek 404 T5 harvester

Characteristics of work environment and soil bearing capacity

Good logging conditions, logging can be done all year round without the use of tracks and without placing logging residues in technological corridors.

Location of demo site



Coordinates of plot centre: X - 445785 Y - 335347 (LKS92)

Figure 25: Location of compartment³².

Stand characteristics before harvesting

Average DBH (cm)	11
Average height (m)	12

³² Background map from Google maps and map of Latvia from www.envirotech.lv



Number of trees (trees per ha ⁻¹)	1917
Growing stock (m ³ ha ⁻¹)	138
Stand composition	10P
Stand age during thinning	41
Dominant species	Scots pine
Stand type	Mr (Vacciniosa)

Stand management targets

To increase forest value by extraction of damaged and small size trees and to ensure favourable growth conditions in the stand. Harvesting is done so to reduce negative impact to environment (avoid ruts formation, mechanical damages of remaining trees and soil compaction). Small dimension trees should be used for biofuel production and from bigger trees standard roundwood assortments (small logs and pulpwood) should be produced.

Stand characteristics after thinning

15
13
15
970
101
10P
Scots pine



Baltic ForBio



Figure 26: Stand characteristics after thinning³³.

Mechanical damages due to thinning

Damage to the remaining trees does not exceed 3%, no ruts have been detected.

Applied work method in thinning

Work order considers thinning to minimal basal area or number of trees according to average tree heigth after thinning.

Distance between technological corridors 20 m with "ghost paths" between the corridors, which are used only by harvester.

Logs are located along the technological corridors. Undergrowth trees are not extracted before mechanized thinning.

The applied work method considers leaving of small dimension trees (including technologic corridors if their $D_{1.3} < 6$ cm, if they are not hampering harvesting operations, but, if such small tree is harvested (cut down) it should be dropped without delimbing in area where it is not becoming an obstacle to harvesting and forwarding operations

Harvesting is done using compact class harvesterVimek 404 T5 acquipped with Keto Forest felling head (10. Fig.). Harvester is equipped with CAT C2.2T engine³⁴ (44 kW, 2700 RPM,); harvester width 1.8 m (with large tyres – 2.15 m), length – 3.35 m; tyre size 405/70-24; MOWI 2046 crane reach distance 4.6 m, weight 400 kg; clearance – 40 cm; harvester

³³ Photo P.O. Johansson.

³⁴ In previous models Kubota V2003T engine.



weight – 4400 kg; fuel consumption – 4 L per hour; control system – Motomit IT.

Forwarding is done using compact class machine Kranman Bison 10000 6WD and middle class forwarder John Deere 810D.



Figure 27: Harvester Vimek 404 T5³⁵.

Harvesting productivity

While producing biofuel in pre-commercial thinning (average extracted tree $D_{1.3}$ 11 cm or 0.07 m³), average productivity of harvester is 7.2 m³ h⁻¹.

³⁵ Photo: P.O. Johansson.